



Transportable
Multi-gas area monitor

Detective+ + A transportable area monitor you can trust

- Loud and bright alarms
- Inherently rugged and reliable
- Wide sensor options including infra-red
- Built-in pump option
- Folding or fixed legs

Used singly or linked together, Detective+ gives a loud and clear alarm providing effective warning of gas hazards. The rugged, water and impact resistant design and clear display make Detective+ the ideal choice for your transportable gas detection needs.

Superb pedigree

- Detective+ is based on the highly successful Triple Plus+ multi-gas monitor which has sold over 55,000 units worldwide

Versatile and user friendly

- Infra-red sensors available
 - allows sampling of potentially high flammable gas levels and CO2
 - infra-red sensors are unaffected by poisoning
- Built-in pump option provides fast response and extra sensor protection
- Display provides clear information, allows identification of gas hazard
- Easy tracking of multiple hazards
- up to 60 hour battery operation
- Wide range of toxic gas sensors available

Extremely loud and clear alarms

- Wailing omni-directional siren, 104 dBA @1 metre
- High intensity red LED clusters provide visual alarm indication
- All linked Detective+ units indicate an alarm sensed by any one unit
- Units actually sensing alarm have faster LED flash
- Audible and visible confidence blip
- Time weighted average alarms for 8 hours and 15 minutes averages

Uniquely rugged, tripod construction

- Detectors are fully protected, even if device is overturned
- Raised detectors prevent water ingress
- Easy and quick to set up
- Folding or fixed leg options provide easy storage and transportation

Transportable multi-gas monitor

Detective +


Specification

Weight	7.5 kg (19lb)		Datalogging	Adjustable sample rate, 100 hours @ 1 minute sample rate (maximum 6000 data points per channel) Logging of events, user and site data																																																									
Dimensions	640 h x 455 w x 455 d mm (25.2 x 17.9 x 17.9 inches)		Menu	Operating menu allows access to setting up of instrument operation Log Menu allows selection of Users and Sites from predefined lists, marking the log file with an event, and start or stop of data logging Configuration Menu allows selection of display and alarm modes, setting of alarms, zero and calibration, and selection of flammable gas correction factors from predefined list .																																																									
Typical measuring ranges and alarm settings (up to four gas measurement channels)		<table border="1"> <thead> <tr> <th></th> <th>Standard Range</th> <th>Typical Alarm Levels</th> </tr> </thead> <tbody> <tr> <td>Flammable gas</td> <td>0 – 100% LEL</td> <td>20% LEL</td> </tr> <tr> <td>Oxygen</td> <td>0 – 25%</td> <td>19% & 23%</td> </tr> <tr> <td>Hydrogen sulphide</td> <td>0 – 50 ppm</td> <td>10 ppm</td> </tr> <tr> <td>Carbon monoxide</td> <td>0 – 500 ppm</td> <td>35 ppm</td> </tr> <tr> <td>Sulphur dioxide</td> <td>0 – 10 ppm</td> <td>2 ppm</td> </tr> <tr> <td>Chlorine</td> <td>0 – 5 ppm</td> <td>0.5 ppm</td> </tr> <tr> <td>Nitrogen dioxide</td> <td>0 – 10 ppm</td> <td>2 ppm</td> </tr> <tr> <td>Phosphine</td> <td>0 – 5 ppm</td> <td>0.5 ppm</td> </tr> <tr> <td>Ammonia</td> <td>0 – 50 ppm</td> <td>25 ppm</td> </tr> <tr> <td>Ammonia</td> <td>0 – 1000 ppm</td> <td>N/A</td> </tr> <tr> <td>Hydrogen (non-flammable levels)</td> <td>0 – 2000 ppm</td> <td>N/A</td> </tr> <tr> <td>Hydrogen cyanide</td> <td>0 – 25 ppm</td> <td>10 ppm</td> </tr> <tr> <td>Hydrogen chloride</td> <td>0 – 10 ppm</td> <td>5 ppm</td> </tr> <tr> <td>Ozone</td> <td>0 – 1 ppm</td> <td>0.3 ppm</td> </tr> <tr> <td>Chlorine Dioxide</td> <td>0-1ppm</td> <td>0.1ppm</td> </tr> <tr> <td>Hydrogen Fluoride</td> <td>0-10ppm</td> <td>1ppm</td> </tr> <tr> <td>Ethylene Oxide</td> <td>0-10ppm</td> <td>5ppm</td> </tr> <tr> <td>Volatile Organic</td> <td>0-100ppm</td> <td>N/A</td> </tr> </tbody> </table>		Standard Range	Typical Alarm Levels	Flammable gas	0 – 100% LEL	20% LEL	Oxygen	0 – 25%	19% & 23%	Hydrogen sulphide	0 – 50 ppm	10 ppm	Carbon monoxide	0 – 500 ppm	35 ppm	Sulphur dioxide	0 – 10 ppm	2 ppm	Chlorine	0 – 5 ppm	0.5 ppm	Nitrogen dioxide	0 – 10 ppm	2 ppm	Phosphine	0 – 5 ppm	0.5 ppm	Ammonia	0 – 50 ppm	25 ppm	Ammonia	0 – 1000 ppm	N/A	Hydrogen (non-flammable levels)	0 – 2000 ppm	N/A	Hydrogen cyanide	0 – 25 ppm	10 ppm	Hydrogen chloride	0 – 10 ppm	5 ppm	Ozone	0 – 1 ppm	0.3 ppm	Chlorine Dioxide	0-1ppm	0.1ppm	Hydrogen Fluoride	0-10ppm	1ppm	Ethylene Oxide	0-10ppm	5ppm	Volatile Organic	0-100ppm	N/A	Battery	6 V, 7.2 Ah Sealed lead acid battery pack Optional 6V, 12Ah high capacity pack
	Standard Range	Typical Alarm Levels																																																											
Flammable gas	0 – 100% LEL	20% LEL																																																											
Oxygen	0 – 25%	19% & 23%																																																											
Hydrogen sulphide	0 – 50 ppm	10 ppm																																																											
Carbon monoxide	0 – 500 ppm	35 ppm																																																											
Sulphur dioxide	0 – 10 ppm	2 ppm																																																											
Chlorine	0 – 5 ppm	0.5 ppm																																																											
Nitrogen dioxide	0 – 10 ppm	2 ppm																																																											
Phosphine	0 – 5 ppm	0.5 ppm																																																											
Ammonia	0 – 50 ppm	25 ppm																																																											
Ammonia	0 – 1000 ppm	N/A																																																											
Hydrogen (non-flammable levels)	0 – 2000 ppm	N/A																																																											
Hydrogen cyanide	0 – 25 ppm	10 ppm																																																											
Hydrogen chloride	0 – 10 ppm	5 ppm																																																											
Ozone	0 – 1 ppm	0.3 ppm																																																											
Chlorine Dioxide	0-1ppm	0.1ppm																																																											
Hydrogen Fluoride	0-10ppm	1ppm																																																											
Ethylene Oxide	0-10ppm	5ppm																																																											
Volatile Organic	0-100ppm	N/A																																																											
Infrared Sensors	Infrared sensors for flammable gas can be supplied as a single range, 0-100% LEL, utilising a single display channel, or as a dual range, 0-100% LEL/0-100% volume, which then occupies two display channels. CO ₂ sensors are supplied as 0-2% volume. Only one IR sensor can be fitted, and IR sensors can only be used in combination with oxygen and toxic sensors		Battery life	Standard instrument: Up to 36 hours assuming flammable/CO ₂ sensor fitted with 7.2Ah battery. Up to 60 hours with optional 12Ah battery pack																																																									
		<table border="1"> <thead> <tr> <th></th> <th>Standard Range</th> <th>Alarm</th> </tr> </thead> <tbody> <tr> <td>Flammable Gas</td> <td>0-100% LEL</td> <td>20% LEL</td> </tr> <tr> <td>Flammable Gas</td> <td>0-100% v/v</td> <td>None</td> </tr> <tr> <td>Flammable Gas</td> <td>available for methane, propane, butane or ethylene</td> <td></td> </tr> <tr> <td>CO₂</td> <td>0-2.0% v/v</td> <td>0.5/1.5% v/v</td> </tr> </tbody> </table>		Standard Range	Alarm	Flammable Gas	0-100% LEL	20% LEL	Flammable Gas	0-100% v/v	None	Flammable Gas	available for methane, propane, butane or ethylene		CO ₂	0-2.0% v/v	0.5/1.5% v/v	Battery charging	Built-in battery charging circuit, dual rate 100 – 120 VAC and 200 - 250 V AC Input options available. (Safe Area operation only) Typical charge time: 12 hours																																										
	Standard Range	Alarm																																																											
Flammable Gas	0-100% LEL	20% LEL																																																											
Flammable Gas	0-100% v/v	None																																																											
Flammable Gas	available for methane, propane, butane or ethylene																																																												
CO ₂	0-2.0% v/v	0.5/1.5% v/v																																																											
Typical response times	Methane 20 s, Oxygen 10 s, typical toxic gas 20 s, IR 30 s		Operating Temperature range	-20°C to +40°C (-4°F to 104°F).																																																									
Expected sensor life	Flammable 5 years, Toxic 3 years, Oxygen 2 year minimum, IR >5 years		Humidity	0 – 95% RH non condensing																																																									
Audible alarms	Wailing, omni-directional siren, 104 dBA @ 1 metre.		Approvals	Europe : ATEX II 2G EEx ib d IIC T4 USA and Canada : Class 1 Division 1 Groups A, B, C, D (Pending)																																																									
Visible alarms	Three large, top-mounted red LED clusters and single red LED on control panel. In alarm mode LED clusters flash in quick succession LED clusters of linked Detectives repeating the alarm, flash more slowly than LED lights on those Detectives sensing the hazard. Slow flashing green LED indicates normal working. Rapid flashing green LED indicates low battery.		Standards	EN50014, EN50020, 94/9/EC UL913 and CSA 22.2																																																									
Display	High contrast LCD with back light 2 lines of 24 characters. Values and units for up to 4 gases displayed simultaneously at current, TWA or peak levels. Low battery, real time and elapsed time, calibration and configuration data also displayed		Ingress protection	IP65																																																									
			EMC	EN 50270																																																									
			PC Interface	Detective+ has an in-built PC interface, which can be connected to the serial port of a computer using the optional RS232 lead. Portables PC software can be used to set alarms, clock, datalogging interval and password. Portables PC also controls datalogging, giving graphical display of instrument log file and allows file export to spreadsheet.																																																									
			Calibration	Detective+ can be routinely calibrated quickly using its internal menu command, Portables PC or the Crowcon CheckBox IMH management system																																																									
			Accessories	Baffle plate (to protect sensors) Interconnecting lead - 10 m standard, longer lengths up to 100m available Computer lead - RS232 serial link Portables PC software Aspirator Manual bulb and 2 m hose, both non-absorbent and hydrocarbon resistant Internal electric sampling pump option includes external water trap and 2m hose, longer lengths available on request																																																									
			Linked Detectives	Up to 12 units can be linked to provide perimeter or area monitoring																																																									